

## **Paslode Bradder– Instructions for use**

### **PRE-START CHECKS**

- Ensure correct sized nails/staples for the gun and job.
- Check worksite for hazards etc.
- Ensure no other person is in direct firing line with the unit. (or behind area being fired into).
- Ensure there are no hidden cables, pipes etc.

### **STARTING PROCEDURE**

1. Insert the battery into the gun & push forward into its locked position.
2. Open the fuel cell compartment by pressing up then pulling out.
3. With the gas outlet stem pointing towards the front of the gun insert the cell assembly.
4. Close the rear cover.
5. Pull the follower handle back to the rear lock position (button will pop out & hold back).
6. Insert a strip of fasteners & release the follower by pushing on the button.

### **OPERATION**

1. Firmly hold gun against timber to be fastened (you will hear the fan motor start & gas is injected into the chamber).
2. Pull the trigger.

### **SAFETY PRECAUTIONS**

- Check safety mechanism is operating correctly.
- Do not tamper with the safety mechanism or other mechanical parts.
- Do not engage in horseplay as the gun can inflict fatal injuries.
- Never assume the gun is empty.
- Never carry your tool with your finger on the trigger.
- Never attempt to clear jams before removing the fuel cylinder & battery.
- Keep your hands away from the area being fastened.

### **REQUIRED SAFETY EQUIPMENT**



Eye Protection



Foot Protection



Hearing Protection



Protective Clothing



Head Protection

If you are collecting the equipment for someone else please make sure this sheet is given to them. If the equipment is being hired for commercial use it should be given to the site supervisor to ensure it is available to all users.