

ELECTRIC SCISSOR LIFTS

0608SE (1930SE)/0608ME (1932ME)

Compliant with CE/ANSI/CSA/EAC/AS/KCS standards

Model	0608SE (1930SE)	0608ME (1932ME)
Dimensions		
Max Working Height (Indoor/Outdoor)	7.8 m (25'7")	7.8 m (25'7")
A Max Platform Height (Indoor/Outdoor)	5.8 m (19')	5.8 m (19')
B Max Horizontal Extension	0.9 m (3')	0.9 m (3')
C Length-Stowed	1.8 m (5'11")	1.8 m (5'11")
D Width-Stowed	0.79 m (2'7.1")	0.81 m (2'8")
E Height-Stowed (Rail Folded)	1.88 m (6'2")	1.88 m (6'2")
E Height-Stowed (Rail Unfolded)	2.14 m (7')	2.14 m (7')
F Wheelbase	1.334 m (4'4")	1.334 m (4'4")
Ground Clearance (Pothole Guard Stowed)	0.075 m (3")	0.075 m (3")
Ground Clearance (Pothole Guard Deployed)	0.024 m (0.95")	0.024 m (0.95")
Platform Dimensions (L×W×H)	1.64 m×0.76 m×1.1 m (5'4.6"×2'6"×3'7")	1.64 m×0.76 m×1.1 m (5'4.6"×2'6"×3'7")
Performance		
Platform Capacity	230 kg (507 lbs)	230 kg (507 lbs)
Extension Platform Capacity	120 kg (265 lbs)	120 kg (265 lbs)
Platform Occupants (Indoor/Outdoor)	2 Persons(Indoor Only)	2 Persons/1 Person
Drive Speed (Stowed)	0~4 km/h (0~2.5 mph)	0~4 km/h (0~2.5 mph)
Drive Speed (Raised)	0~0.8 km/h (0~0.5 mph)	0~0.8 km/h (0~0.5 mph)
Lift Time (Unloaded)	15 s~20 s	15 s~20 s
Lower Time (Unloaded)	25 s~30 s	25 s~30 s
Gradeability	25%	25%
Max Allowable Inclination (front-to-back/side-to-side)	3°/1.5°	3°/1.5°
Turning Radius (Inside/Outside)	0/1.49 m (0/4'10.7")	0/1.49 m (0/4'10.7")
Tyre Size/Type	323×100 mm (12.7×4")/solid	323×100 mm (12.7×4")/solid
Power		
Drive×Steer	2 WD×2 WS	2 WD×2 WS
Power Source (V/kW)	24 V/2.2 kW	24 V/2.2 kW
Drive Motor (V/kW)	24 V DC/0.6 kW 24 V AC/0.6 kW	24 V DC/0.6 kW 24 V AC/0.6 kW
Hydraulic Tank Capacity	6L (1.3gal(UK)/ 1.6gal(US))	6L (1.3gal(UK)/ 1.6gal(US))
Batteries	24V, 220 Ah (Lead acid battery)	24V, 220 Ah (Lead acid battery)
Charger (Input/Output)	100~240 V AC/30 A	100~240V AC/30 A
Weight		
Weight (Indoor/Outdoor)	1,575 kg (3,473 lbs)(Indoor Only)	1,575 kg (3,473 lbs)
Standards Compliance	CE/ANSI/CSA/EAC	CE/ANSI/CSA/EAC/KCS

